


TECHNICAL SPECIFICATIONS NT2 HYBRID



10 mm ³/₈" 34 mm 1 ⁵/₁₆"

NT2 HYBRID

| | |
|--|--------------------|
| Max. operating pressure | 12 bar |
| Max. lifting capacity | 26 tonnes |
| Max. lifting capacity at max. lifting height | 6.2 tonnes |
| Insertion height | 10 mm / 34 mm |
| Max. lifting height | N x 275 mm |
| Effective lifting height | N x 241 mm |
| Volume | 22 liter |
| Max. air contents | 286 liter |
| Temperature range | -20 °C till +65 °C |
| Weight | 6.5 kg |
| Safety factor | > 4 |

| ACCESSORIES | Art. Nr. | ACCESSORIES | Art. Nr. |
|---|-----------|------------------------------------|-----------|
| Valise NT2 Hybrid | 8700.0310 | Shut off hose 2m / red / rubber | 8700.1352 |
| Accessory case | 8700.0795 | Shut off hose 2m / yellow / rubber | 8700.1357 |
| Regulator c/w 2m black rubber inlet hose | 8700.0570 | Shut off hose 2m / green / rubber | 8700.1362 |
| Handheld dual controller 12 bar | 8700.0552 | Shut off hose 2m / blue / rubber | 8700.1367 |
| Dual air cylinder connector | 8700.0620 | Shut off hose 2m / red | 8700.1258 |
| Delivery hose 12 bar / 8m / red / rubber | 8700.1332 | Shut off hose 2m / yellow | 8700.1263 |
| Delivery hose 12 bar / 8m / yellow / rubber | 8700.1337 | Shut off hose 2m / green | 8700.1273 |
| Delivery hose 12 bar / 8m / green / rubber | 8700.1342 | Shut off hose 2m / blue | 8700.1283 |
| Delivery hose 12 bar / 8m / blue / rubber | 8700.1347 | Connector key | 8700.2008 |
| Delivery hose 12 bar / 10m / red | 8700.1107 | Solid quick connector | 8700.2050 |
| Delivery hose 12 bar / 10m / yellow | 8700.1112 | PowerPlate | 8420.0060 |
| Delivery hose 12 bar / 10m / green | 8700.1117 | PowerPlate plug | 8700.2075 |
| Delivery hose 12 bar / 10m / blue | 8700.1122 | Floor mat | 8700.0715 |
| | | Floor mat plug | 8700.2040 |



Information contained in this document is believed to be accurate. However RESQTEC does not guarantee the completeness or accuracy of any of the published information.



RESQTEC Zumro B.V.
 Meer en Duin 82 | 2163 HC Lisse, the Netherlands

T +31 (0)252 419002
E info@resqtec.com

F +31 (0)252 411794
W www.resqtec.com

