


TECHNICAL SPECIFICATIONS NT4 HYBRID



10 mm 3/8" 48 mm 1 7/8"

NT4 HYBRID

Max. operating pressure	12 bar
Max. lifting capacity	70 tonnes
Max. lifting capacity at max. lifting height	9.5 tonnes
Insertion height	10 mm / 48 mm
Max. lifting height	N x 440 mm
Effective lifting height	N x 392 mm
Volume	99 liter
Max. air contents	1,287 liter
Temperature range	-20 °C till +65 °C
Weight	15.5 kg
Safety factor	> 4

ACCESSORIES	Art. Nr.	ACCESSORIES	Art. Nr.
Valise NT4 Hybrid	8700.0320	Shut off hose 2m / red / rubber	8700.1352
Accessory case	8700.0795	Shut off hose 2m / yellow / rubber	8700.1357
Regulator c/w 2m black rubber inlet hose	8700.0570	Shut off hose 2m / green / rubber	8700.1362
Handheld dual controller 12 bar	8700.0552	Shut off hose 2m / blue / rubber	8700.1367
Dual air cylinder connector	8700.0620	Shut off hose 2m / red	8700.1258
Delivery hose 12 bar / 8m / red / rubber	8700.1332	Shut off hose 2m / yellow	8700.1263
Delivery hose 12 bar / 8m / yellow / rubber	8700.1337	Shut off hose 2m / green	8700.1273
Delivery hose 12 bar / 8m / green / rubber	8700.1342	Shut off hose 2m / blue	8700.1283
Delivery hose 12 bar / 8m / blue / rubber	8700.1347	Connector key	8700.2008
Delivery hose 12 bar / 10m / red	8700.1107	Solid quick connector	8700.2050
Delivery hose 12 bar / 10m / yellow	8700.1112	PowerPlate	8420.0060
Delivery hose 12 bar / 10m / green	8700.1117	PowerPlate plug	8700.2075
Delivery hose 12 bar / 10m / blue	8700.1122	Floor mat	8700.0715
		Floor mat plug	8700.2040



Information contained in this document is believed to be accurate. However RESQTEC does not guarantee the completeness or accuracy of any of the published information.



RESQTEC Zumro B.V.
 Meer en Duin 82 | 2163 HC Lisse, the Netherlands

T +31 (0)252 419002
E info@resqtec.com

F +31 (0)252 411794
W www.resqtec.com

