

# TECHNICAL SPECIFICATIONS

## POSITIVE AIRBLAST 20"



### POSITIVE AIRBLAST 20" ELECTRIC

Dimensions (L x W x H)	660 x 640 x 590 mm
Motor	1 HP / 0.75kW / 220V totally enclosed
Operational weight	35 kg
Speed	1,750 RPM
Airflow	17,312 m3/hour
Open airflow <sup>1</sup>	28,169 m3/hour
Start	4,000W
Run	1,500W
Air cone guard	Yes
Tilting positions	5 positions
7-Point air blade	Yes
Transportation	Full width handle and rubber tires

### ACCESSORIES

#### Art. Nr.

Foam generator	6210.0018
Flexible duct 3 m incl. strap	6140.0061
Flexible duct 6 m incl. strap	6140.0062
Water mist system for Cone guard	6500.0022
Water mist system for Stream shaper guard	6500.0122
Stream shaper guard	

<sup>1</sup>Maximum is a theoretical flow



Information contained in this document is believed to be accurate. However RESQTEC does not guarantee the completeness or accuracy of any of the published information.



**RESQTEC Zumro B.V.**  
Meer en Duin 82 | 2163 HC Lisse, the Netherlands

**T** +31 (0)252 419002  
**E** info@resqtec.com

**F** +31 (0)252 411794  
**W** www.resqtec.com

**RESQTEC®**