

TECHNICAL SPECIFICATIONS

POSITIVE AIRBLAST 20"



POSITIVE AIRBLAST 20" VARIABLE SPEED

Dimensions (L x W x H)	660 x 640 x 590 mm
Motor	1 HP / 0.75kW / 220V variable speed
Operational weight	34 kg
Speed	2,400 RPM
Airflow	25,672 m3/hour
Open airflow ¹	41,267 m3/hour
Start	2,000W
Run	1,500W
Air cone guard	Yes
Tilting positions	5 positions
7-Point air blade	Yes
Transportation	Full width handle and rubber tires

ACCESSORIES

Art. Nr.

Foam generator	6210.0018
Flexible duct 3 m incl. strap	6140.0061
Flexible duct 6 m incl. strap	6140.0062
Water mist system for Cone guard	6500.0022
Water mist system for Stream shaper guard	6500.0122
Stream shaper guard	

¹Maximum is a theoretical flow



Information contained in this document is believed to be accurate. However RESQTEC does not guarantee the completeness or accuracy of any of the published information.



RESQTEC Zumro B.V.
Meer en Duin 82 | 2163 HC Lisse, the Netherlands

T +31 (0)252 419002
E info@resqtec.com

F +31 (0)252 411794
W www.resqtec.com

RESQTEC®